



“ Ready to Make an  
IMPACT ”



*AC-7777 Chetak*







## Technical Specification of AC-7777 Chetak

Article	AC – 7777 Chetak <b>Allen Cooper Make</b>
Construction	Direct Injection Dual Density PU.
Marking	ISI Marked as per IS : 15298 (Part – II ) : 2016 CM/L : 4858790
Upper	Made From Buff Barton Printed Leather of 1.822 mm
Toe Impact	Steel Toe Cap 200 ±4J
Lining	Non – Woven Felt for comfortability
Sole	DIP Dual Density Sole, having thickness (Cleat Height) of 6 mm, Flexing Resistance (30,000 Cycles) – Cut growth is below 4mm. Hydrolysis (1,50,000 Cycles) – Cut growth is below 6 mm Resistant to Fuel Oil – below 12%. Weight of sole 250±5gms per odd of 8 size.
Thread	Nylon 3 & 6 Ply
Eyelets	4 Sets of Eyelets for better Grip.
Laces	Nylon 90 cm (min.) Round with breaking strength 50-60 kg.
Fining	Elegant and spray finish
Special Features	<ul style="list-style-type: none"><li>❖ Highly breathable Leather upper.</li><li>❖ Reflective material visible at workstation.</li><li>❖ Cushioned inter lining &amp; padded collar.</li><li>❖ Abrasion, fuel Oil and Slip resistant outsole.</li><li>❖ Antistatic (100KΩ - 1000MΩ)</li><li>❖ Resistant to Hot Contact upto 120°C for 1 minute.</li></ul>



IS:15298



Part-2

CM/L-9715086